

CRYOGENIC RANGE

SOFT SEATED



SERIES	MATERIAL CONST.	CONST. TYPE	END CONNECT.	ASME CL150 DIN PN16	ASME CL300 DIN PN40	ASME CL600 DIN PN100	ASME CL1500 DIN PN250	ASME CL2500 DIN PN400
CXF	Cast	3-piece Floating	THRD / Weld / Nipple*	6"(150) FB	2"(50) to 4"(100) FB 2½"(65) to 4"(100) RB**	⅜"(10) to 1½"(40) FB ½"(15) to 2"(50) RB	-	-
CCF ASME		Split-body Floating	FLG	½"(15) to 6"(150) FB	½"(15) to 6"(150) FB	½"(15) to 2"(50) FB	-	-
CCF DIN		Split-body Floating	FLG	DN15 to DN150 FB	DN15 to DN150 FB	-	-	-
CQF		Multiport Floating	THRD / Weld / FLG	-	2"(50) FB	½"(15) to 1½"(40) FB	-	-
CCT		Split-body Trunnion	FLG	4"(100) to 12"(300) FB	4"(100) to 12"(300) FB	-	-	-
CDXF		DBB Floating	THRD / Weld / Nipple*	6"(150) FB	2"(50) to 4"(100) FB 2½"(65) to 4"(100) RB**	⅜"(10) to 1½"(40) FB ½"(15) to 2"(50) RB	-	-
CDCF ASME		DBB Floating	FLG	½"(15) to 6"(150) FB	½"(15) to 6"(150) FB	½"(15) to 2"(50) FB	-	-
CDCF DIN		DBB Floating	FLG	DN65 to DN150 FB	DN15 to DN150 FB	-	-	-
CXFD		Diverter Floating	THRD / Weld / Nipple*	-	-	½"(15) to 1½"(40) FB	-	-
CHF5/6	Barstock	3-piece Floating	THRD / Weld	-	-	-	¼"(8) to 2"(50) FB ¾"(20) to 2"(50) RB	¼"(8) to 1"(25) SB
CVT	Forged / Barstock	3-piece Trunnion	FLG / Weld	2"(50) to 12"(300) FB	2"(50) to 12"(300) FB	2"(50) to 12"(300) FB	2"(50) to 6"(150) FB	2"(50) to 4"(100) FB
CBFD		Diverter Floating	FLG	2½"(65) to 6"(150) FB	½"(15) to 6"(150) FB	½"(15) to 2"(50) FB	-	-
CSFD		Diverter Floating	THRD / Weld / Nipple*	6"(150) FB	2"(50) to 4"(100) FB 2½"(65) to 4"(100) RB**	⅜"(10) to 1½"(40) FB ½"(15) to 2"(50) RB	-	-

*Nipple only available in buttweld full bore version; **Reduced bore only available in Butt weld version.