

SANITARY RANGE

SOFT SEATED



SERIES	MATERIAL CONST.	CONST. TYPE	END CONNECT.	ASME CL150 DIN PN16	ASME CL300 DIN PN40	ASME CL400 DIN PN63	ASME CL600 DIN PN100	ASME CL800 DIN PN138
RP ASME	Barstock	3-piece Floating	OBW Clamp	2½"(65) to 6"(150) TB	½"(15) to 2"(50) TB	-	-	-
RP DIN		3-piece Floating	OBW Clamp	DN65 to DN150 FB	DN10 to DN50 TB	-	-	-
RP ISO		3-piece Floating	OBW Clamp	DN65 to DN150 FB	DN8 to DN50 FB	-	-	-
RPD ASME		Diverter* Floating	OBW Clamp	2½"(65) to 6"(150) TB	½"(15) to 2"(50) TB	-	-	-
RPD DIN		Diverter* Floating	OBW Clamp	DN65 to DN150 FB	DN10 to DN50 TB	-	-	-
MP ASME		Multiport* Floating	OBW Clamp	2½"(65) to 4"(100) TB	½"(15) to 2"(50) TB	-	-	-
MP DIN		Multiport* Floating	OBW Clamp	DN65 to DN100 FB	DN10 to DN50 FB	-	-	-
MP ISO		Multiport* Floating	OBW Clamp	DN65 to DN100 FB	DN10 to DN50 FB	-	-	-
XP ASME	Cast	3-piece Floating	EBW Clamp	2½"(65) to 6"(150) TB	½"(15) to 2"(50) TB	-	-	-
XP DIN		3-piece Floating	EBW Clamp	DN65 to DN150 FB	DN15 to DN50 TB	-	-	-
XP ISO		3-piece Floating	EBW Clamp	DN65 to DN150 FB	DN8 to DN50 FB	-	-	-
QP ASME		Multiport* Floating	EBW Clamp	-	½"(15) to 2"(50) TB	-	-	-
QP DIN		Multiport* Floating	EBW Clamp	-	DN10 to DN50 FB	-	-	-
QP ISO		Multiport* Floating	EBW Clamp	-	DN10 to DN50 FB	-	-	-
LP ASME		3-piece Floating	OBW Clamp	-	½"(15) to 2"(50) TB	-	-	-
CFP ASME		Split-body Floating	FLG	½"(15) to 8"(200) FB	½"(15) to 8"(200) FB	-	½"(15) to 2"(50) FB	-
CFP DIN		Split-body Floating	FLG	DN65 to DN200 FB	DN15 to DN200 FB	-	-	-
XFP		3-piece Floating	THRD / Weld / Nipple	6"(150) FB	4"(100) FB	2½"(65) to 3"(80) FB 3"(80) to 4"(100) RB	1½"(40) to 2"(50) FB 2"(50) to 2½"(65) RB	¾"(10) to 1¼"(32) FB ½"(15) to 1½"(40) RB
QFP ASME		Multiport* Floating	THRD / Weld / FLG	½"(15) to 2"(50) FB	½"(15) to 2"(50) FB	-	½"(15) to 2"(50) FB ¾"(20) to 2"(50) RB**	-
QFP DIN		Multiport* Floating	FLG	-	DN15 to DN50 FB	-	-	-

SERIES	MATERIAL CONST.	END CONNECT.	DIMENSIONS
CVR	Barstock	OBW Clamp	½"(15) to 4"(100)
CHR		OBW Clamp	½"(15) to 4"(100)
SG		OBW Clamp	½"(15) to 4"(100)

*Multiport valves are limited up to 20 bar. **Only available in Welded and Threaded ends.